

HOT ROD 1450

1. Front Engine FWD. Rear engine RWD
2. Modified saloons/pickup up to 1450cc maximum. Single engine only.
3. Multi valve, Multi point fuel injection is permitted.
4. Engine modifications are free.
5. RWD rear engine the rear bulkhead can finish at the bottom of the rear side window aperture, with a shield at 45deg. To shield the drivers back.
6. All chains on chain driven cars must have adequate protection from drivers and other competitors.
7. FWD or rear engine modified saloons and manufactured pickups up to 1450cc maximum, including overbore, no limit to over boring as long as capacity does not exceed the 1450cc maximum limit.
8. No turbo/super charging, or other forced induction.
9. All other modifications are free.
10. Oil coolers must not be in window aperture
11. Wheel width must not exceed 10" wide.
12. Tyre size and type are free.
13. Space frames are permitted.
14. The position of the engine and gearbox may be moved from front to rear or rear to front but must remain engine over driven wheel.
15. Full composite bodyshell is permitted.
16. Composite bodied cars fitted with space frame must have steel plate welded to roll cage of minimum thickness 16swg over the driver's head.
17. Composite material replacement bonnets, boots and doors are permitted.
18. Any composite must not exceed ¼" (6mm) thick.
19. Shock absorbers may be up rated and the mountings relocated.
20. Electronic or any other form of traction control is not permitted.